



Superspray 3802

Productsheet

Description

SABA Superspray 3802 is a one-component water-based sprayable adhesive for the foam converting industry. SABA Superspray 3802 is ideal for the bonding of foam substrates and the production of furniture and mattresses.

Special properties

- Very high initial tack
- Flexible bond line
- Ideal for foam to wood and foam to non-wovens
- High initial tack at foam-wood connections
- Good repositionability
- Solvent-free

Method of use

Apply by spray gun. Please spray both parts, bond within 12 minutes and press well. Spraying pressure about 2 bar and spraying distance at least 30 cm.

Technical data

Viscosity at 23 °C	: approx. 500 mPa.s
Density	: approx. 1087 kg/m ³
Solids content	: approx. 55%
Open time	: approx. 12 minutes
Curing time	: approx. 24 hours
Coverage	: depending on application
Clean with	: SABA Cleaner AV
Work temperature	: minimum + 15 °C and maximum + 25 °C
Storage temperature	: minimum + 5 °C and maximum + 35 °C (frost sensitive)
Temperature resistance	: approx. + 65 °C
Shelf life	: 6 months in unopened packing

Order information

Packing	: 1000 litres container, contents 1050 kg
Colour	: natural, pink and yellow

Safety recommendations

See the corresponding material safety data sheet.

Note:

- SABA Superspray 3802 is a test product which implies:
- the delivery time could exceed the standard 10 working days
 - product specifications are subject to alterations
 - this product could be withdrawn without further notice

SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, PO Box 3, NL-7090 AA Dinxperlo, the Netherlands, Tel +31 (0) 315 658999, Fax +31 (0) 315 653207, E-mail info@saba.nl, Internet www.saba.nl.

Our recommendations and instructions for use are based on the present status of know-how and technique. Clients and users should evaluate our products by themselves, with regard to utilization and requirements of their own choice. We shall take no responsibility in case our products are not being used subject to our recommendations and/or instructions for use. Furthermore, General Terms and Conditions of the Dutch Association "Nederlandse Vereniging van Rubber en Kunststoffabrikanten of November 1, 1992", will apply to our recommendations, instructions for use and the delivery of our products.

Version: 2008-09-26